

MANNOL®

PASSENGER CAR MOTOR OIL

Hybrid SP

Full Bi-Synthetic (PAO + Esters)

SAE 0W-16

API SP (RC)

LSAC GF-6B

HYBRID RECOMMENDED



1 L · 5 L

DESCRIPTION

Innovative energy-saving low-viscosity engine oil of the latest generation on a bi-synthetic (PAO + esters) basis for modern gasoline engines.

Designed in accordance with the latest API SP and ILSAC GF-6 standards, it is especially recommended for hybrid cars, but it is also suitable for non-hybrid, requiring oils of such viscosity and with similar performance properties.

PRODUCT PROPERTIES

- | | |
|---|--|
| <p>01 Unsurpassed fuel economy in all modes due to ultra-low kinematic (at 100°C) and reduced high-temperature viscosity HTHS (at 150°C) and exceptional antifriction properties;</p> | <p>02 Highly effective additive package and low-viscosity bi-synthetic base provide confident cold start in the most severe conditions, which significantly reduces starting engine wear and idle wear;</p> |
| <p>03 It does not form deposits in the combustion chamber, especially in the area of piston rings and valves, and due to its excellent washing and dispersing properties and the highest thermal oxidative stability, it effectively fights all types of deposits in all other engine components and keeps them clean throughout the entire interval between replacements;</p> | <p>04 The ester oil components provide excellent anti-wear properties due to the exceptional strength of the oil film even at extreme operating temperatures, which, combined with excellent pumpability, significantly increases engine life even in "start-stop" driving modes;</p> |
| <p>05 For turbocharged engines with direct injection, the unique formulation of the oil completely reduces to zero the effect of premature ignition of the LSPI (Low Speed Pre-Ignition) fuel mixture;</p> | <p>06 Neutral to sealing materials. It eliminates leaks, in combination with reduced volatility provides extremely low oil consumption and has an increased drain interval;</p> |
| <p>07 Significantly extends engine life. It is used in engines with extended oil change intervals (Long Life) and conventional.</p> | |

APPLICATIONS

Designed for gasoline engines of cars, light SUVs, vans and light trucks, where the performance level of API SP / ILSAC GF-6 and lower is required. Recommended for cars: TOYOTA, HONDA, NISSAN, SUBARU, CHRYSLER, MITSUBISHI, MAZDA, SUZUKI.

The oil is not suitable for use in heavy trucks and similar vehicles!

RECOMMENDATION

HONDA Ultra Green

HONDA 08215-99974

HONDA 08216-99974

HONDA 08232-P99S1LHE

MITSUBISHI MZ102661

MITSUBISHI MZ102662

MITSUBISHI DiaQueen ECO Plus

NISSAN Hybrid engine KLANM-01A04 Extra Save X Eco

TOYOTA 08880-11005

* COMPLY WITH THE MANUFACTURER'S INSTRUCTIONS PROVIDED IN THE USER'S MANUAL.

CODES & AVAILABLE PRESENTATIONS

MN7920-5

MANNOL Hybrid SP SAE 0W-16 API SP (RC)

5 L

MN7920-1

MANNOL Hybrid SP SAE 0W-16 API SP (RC)

1 L

SPECIFICATIONS

SPECIFICATION	VALUE
SAE	0W-16
API	SP (RC)
LSAC	GF-6B



INFORCA
INTERNATIONAL
Oil & Car Care Products

DISTRIBUTED BY

Inforca International · Oil & Car Care Products

1862 NW 82nd Ave, Doral, FL 33126 +1 (305) 910 0282

www.inforcainternational.com

GOT QUESTIONS?

Get in touch with us!

