

MANNOL®

MULTIPURPOSE LITHIUM GREASE

Universal Multipurpose Grease MP2 Ester

Lithium Soap · Ester Fortified

NLGI 2

DIN 51502 K2K-30

-30 °C TO +120 °C



400 G

DESCRIPTION

Multipurpose grease for general use based on highly refined mineral oils with lithium soap-based thickener and the addition of synthetic esters, special anti-oxidative as well as anti-corrosive additives.

Developed for use in all types of mobile machinery as well as for general industrial applications.

PRODUCT PROPERTIES

- | | |
|---|---|
| <p>01 The presence of synthetic esters significantly increases the anti-wear, anti-seize and anti-friction properties of the grease;</p> | <p>02 Keeps its performance properties from -30 °C to +120 °C, which increases the service life of the bearings;</p> |
| <p>03 Has good water resistance;</p> | <p>04 Protects reliably against corrosion in soiled environments for long periods of operation;</p> |
| <p>05 Excellent mechanical and oxidation stability;</p> | <p>06 The consistency of the grease remains constant during long-term storage. Shelf life 5 years from the date of production.</p> |

APPLICATION

High-speed slide and roller bearings;

Bearings of electric motors and electric generators, pumps etc.;

Closed bearing units with lifetime lubrication;

Developed for use in all types of mobile machinery as well as for general industrial applications.

* OBSERVE THE MANUFACTURER'S INSTRUCTIONS IN THE OPERATING MANUAL OF THE MACHINERY!

CLASSIFICATION

CLASSIFICATION	VALUE
NLGI	2
DIN 51502	K2K-30
Operating range	-30 °C to +120 °C
Shelf life	5 years

CODES & AVAILABLE PRESENTATIONS

8106	8027-01	8027-023	8027-04	8027-08	8027	8047	8027-18
CODE AS LISTED	100 G	230 G	400 G	800 G	4.5 KG	9 KG	18 KG

GOT QUESTIONS?

