

MANNOL®

MANUAL TRANSMISSION GEAR OIL

Unigear

Full Synthetic

SAE 75W-80

API GL-4/GL-5 LS

MIL L 2105 C

ENERGY CONSERVING



20 L

DESCRIPTION

A universal energy-conserving synthetic gear oil. It may be used in all manual transmission devices, including 5- and 6-speed synchronized manual transmissions, transmissions with an incorporated differential of front wheel drive vehicles, transfer cases and main gears, including hypoid.

It was developed specially for ensuring the protection of the technical equipment and receiving the maximum return regardless of its operating conditions.

PRODUCT PROPERTIES

- 01** The low-viscosity synthetic base of the highest quality with ideal viscosity in the required range of temperatures in combination with a latest-generation additive package ensures superior antifriction properties thus ensuring a significant fuel economy and the smoothness of the transmission shift;
- 02** Due to its unique composition, it ensures excellent antiwear and anti-scuffing properties that significantly extend the expected life of the technical equipment in all, even the most extreme, modes of operation in a wide range of ambient temperatures;
- 03** The synthetic base ensures superior low-temperature properties that ensure an easy starting, reliable lubrication, as well as an easy and precise transmission shift at the lowest (up to -45 °C) ambient temperatures;
- 04** Due to the synthetic base, it has a high stability to oxidation that allows increasing the time between oil changes and reducing equipment maintenance costs;
- 05** It is compatible with all structural metals and alloys, as well as with sealing materials thus allowing reducing the expenses for spare parts.

APPLICATIONS

It is intended for all types of technical equipment: highway (freight trucks, buses, etc.), off-road (construction, mining, agricultural) and special vehicles produced by European, American and Asian manufacturers, in which the required level of operating properties is GL-4 and lower and/or GL-5.

RECOMMENDATION

FORD WSD-M2C200-C

MACK GO-J Plus

PSA B71 2330

* COMPLY WITH THE MANUFACTURER'S INSTRUCTIONS PROVIDED IN THE USER'S MANUAL.

CODES & AVAILABLE PRESENTATIONS

MN8109-20

MANNOL Unigear SAE 75W-80 API GL-4/GL-5 LS

20 L

SPECIFICATIONS

SPECIFICATION	VALUE
SAE	75W-80
API	GL-4/GL-5 LS
MIL	L 2105 C



INFORCA
INTERNATIONAL
Oil & Car Care Products

DISTRIBUTED BY

Inforca International · Oil & Car Care Products

1862 NW 82nd Ave, Doral, FL 33126 +1 (305) 910 0282

www.inforcainternational.com

GOT QUESTIONS?

Get in touch with us!



02 / 02