

MANNOL®

AUTOMATIC TRANSMISSION FLUID

Automatic Plus ATF

Synthetic Based

Dexron III

GM DEXRON III H

FORD MERCON V



1 L · 4 L · 208 L · 1000 L

DESCRIPTION

A universal all-season synthetic-based transmission fluid (ATF) for automatic gearboxes, hydraulic converters, hydraulic power steering systems, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles.

It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by GM and Ford groups.

PRODUCT PROPERTIES

- 01** The highest-quality low-viscosity synthetic base with a consistent high viscosity index in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C) temperatures in winter and ensures a stable oil film under extreme loads and high temperatures in summer;
- 02** The high-technology combination of additives ensures good antifriction properties for gear couplings and required friction properties for friction elements thus ensuring a significant fuel economy, a continuous and smooth transmission shift and an extended service life of all transmission elements. It ensures a coordinated and smooth operation of the clutch. It prevents scuffing;
- 03** It has an increased thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits, increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;
- 04** It protects metal parts from ferrous and non-ferrous alloys (especially radiators) from corrosion when both in and not in operation;
- 05** It effectively resists aeration and foam formation;
- 06** It ensures a compatibility with all sealing materials, prevents them from swelling, hardening and shrinking thus allowing reducing the costs for spare parts and prevents leakages. It effectively protects fluoroelastomer seals of heavy equipment;
- 07** It reduces noise.

APPLICATIONS

It is recommended for automatic gearboxes of passenger cars and commercial vehicles requiring the ATF Type Dexron-III H/G/F or Dexron-II E or FORD MERCON V quality oil.

It is designed for the majority of automatic gearboxes for General Motors, Ford Company and other brands manufactured up to 2006. Colour: red.

* COMPLY WITH THE MANUFACTURER'S INSTRUCTIONS PROVIDED IN THE USER'S MANUAL.

RECOMMENDATIONS

SPECIFICATION	VALUE
ALLISON	C4
ALLISON	TES 295
ALLISON	TES 468
CATERPILLAR	TO-2
FORD	Mercon V
FORD	ESP-M2C138-CJ
FORD	ESP-M2C166-H
GM	Dexron III H
GM	Dexron III G
GM	Dexron III F
MB	236.91
VOITH	H 55.6335.xx (G607)
ZF	TE-ML 09
ZF	TE-ML 04D
ZF	TE-ML 14C
ZF	TE-ML 16M
ZF	TE-ML 11
ZF	TE-ML 14

CODES & AVAILABLE PRESENTATIONS

MN8206-1

MANNOL Automatic Plus ATF
Dexron III

1 L

MN8206-4

MANNOL Automatic Plus ATF
Dexron III

4 L

MN8206-DR

MANNOL Automatic Plus ATF
Dexron III

208 L DRUM

MN8206-IBC

MANNOL Automatic Plus ATF
Dexron III

1000 L IBC



INFORCA
INTERNATIONAL

Oil & Car Care Products

DISTRIBUTED BY

Inforca International · Oil & Car Care Products

1862 NW 82nd Ave, Doral, FL 33126 +1 (305) 910 0282

www.inforcainternational.com

GOT QUESTIONS?
Get in touch with us!



02 / 02