



DIESEL ENGINE OIL

Synthetic Blend Heavy-Duty SAE 15W-40

API CK-4/SN

ACEA E9

HEAVY-DUTY



5 QT PRESENTATION

DESCRIPTION

- Specially formulated to ensure superior lubrication and long life.
- Shown to be versatile as well as able to meet the grueling demands of today's low emission diesel engines, as well as the older models which are using both low and high sulfur fuels.
- Premium grade diesel engine oil that provides protection and oxidation resistance for highly rated diesel engines running in severe service conditions.
- Recommended for use in a variety of heavy duty uses as well as operating environments.

FEATURES & BENEFITS

- | | |
|--|--|
| <p>01 Performs well in low emission diesel engines which increase the demands on engine lubricants.</p> | <p>02 Delivers the best performance in late model engines, as well as older engines.</p> |
| <p>03 Excellent soot handling capabilities.</p> | <p>04 Exemplary thermal stability and oxidation control.</p> |
| <p>05 Contains properties which provide anti-wear and anti-scuff.</p> | <p>06 Contains extended TBN reserves which provide improved acid neutralization and corrosion protection.</p> |
| <p>07 Maximizes oil flow to the critical bearing surfaces during start up.</p> | <p>08 Has stay-in-grade shear stability.</p> |
| <p>09 Extended drain capabilities- excellent water tolerance.</p> | |

APPLICATIONS

- On the highway applications for light and heavy duty trucking.
- Off the highway applications such as trucking, construction, agriculture and quarrying.
- Various mixed fleet applications.

MEETS REQUIREMENTS OF

API CK-4**, CJ-4, CI-4 Plus, CI-4, CH-4

API SN**, SN, SM, SL, SJ

ACEA E11-2022, E7-2022, (E9-16)

Allison TES 439

Caterpillar ECF-3, ECF-2

Cummins CES 20086**, CES 20081

Daimler MB 228.31 (DTFR 15C100)**

Detroit Diesel DFS 93K222**, DFS 93K218

DUETZ DQC III-18 LA (DQC III-10 LA)

Ford WSS-M2C171-F1

JASO DH-2^^

Mack EOS-4.5, EO-O Premium Plus, EO-N

MAN M3775 (M3575)

MTU Category (Type) 2.1

Renault RLD-3, (Renault RLD-4, Renault RLD VI-4)

Volvo VDS-4.5**, VDS-4, VDS-3 **LICENSED. APPROVED BY ENGINE MANUFACTURER. ^^MEETS ENGINE TEST REQUIREMENTS.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

CODES & AVAILABLE PRESENTATIONS

PG206-BLK

PureGuard Synthetic Blend Heavy-Duty SAE 15W-40

BULK

PG206-5GL

PureGuard Synthetic Blend Heavy-Duty SAE 15W-40

5 GAL

PG206-5QT

PureGuard Synthetic Blend Heavy-Duty SAE 15W-40

5 QT

PERFORMANCE AT A GLANCE

VISCOSITY INDEX

139

NOACK, %

9.2

COLD CRANK, CP AT -20°C

6,046

TYPICAL TEST DATA

SAE GRADE

15W-40

Specific Gravity @ 60°F

0.8758

Viscosity, Kinematic cSt at 40°C

116.6

Viscosity, Kinematic cSt at 100°C

15.5

Viscosity Index

139

Flash Point, (°F)

440

Pour Point, °C (°F)

-33

Cold Crank, cP at -20°C

6,046

Color

3.0

Noack, %

9.2

TBN

10.6

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.



INFORCA
INTERNATIONAL
Oil & Car Care Products

DISTRIBUTED BY

Inforca International · Oil & Car Care Products

1862 NW 82nd Ave, Doral, FL 33126 +1 (305) 910 0282 www.inforcainternational.com



02 / 02