



Synthetic DOT 3

ISO 4925 CLASS 3



REFERENCE PHOTOGRAPH

SYNTHETIC DOT 3 HYDRAULIC BRAKE FLUID is a specially compounded preparation designed solely for use in motor vehicle braking systems. It is for use in all vehicles, where grade DOT 3 is recommended by manufacturers. SYNTHETIC DOT 3 HYDRAULIC BRAKE FLUID far exceeds DOT 3 and other federal and SAE specifications for motor vehicle brake fluid. Mixes with all other approved brake fluids, and is suitable for use in ATE, Girling, Lockheed and other systems.

05 Avoid spilling on vehicle finish. If spilled, wipe off immediately with clean cloth.

APPLICATIONS

SYNTHETIC DOT 3 HYDRAULIC BRAKE FLUID is a DOT 3 motor vehicle brake fluid for disc and drum brakes. It meets Federal Motor Vehicle Safety Standard No. 116, SAE J1703, and ISO 4925 (Class 3). It is certified by ABIC Testing Laboratories, Inc.

* ALWAYS CONSULT YOUR OWNER’S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

PROPERTIES	PRODUCT SPECIFICATIONS
Specific Gravity @60°F	1.01 – 1.05
Dry Boiling Point, °F	450 Minimum
Wet Boiling Point, °F	284 Minimum
Color	Colorless to Amber

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

CODES & AVAILABLE PRESENTATIONS

PG601-1QT

PureGuard Synthetic DOT 3

1 QT



INFORCA
INTERNATIONAL
Oil & Car Care Products

DISTRIBUTED BY

Inforca International · Oil & Car Care Products

1862 NW 82nd Ave, Doral, FL 33126 +1 (305) 910 0282 www.inforcainternational.com

