



TRACTOR HYDRAULIC FLUID

XL Tractor Hydraulic Fluid

J20C

QUATROL APPROVED



5 GAL PRESENTATION

DESCRIPTION

XL Tractor Hydraulic Fluid is formulated specially for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment which employs a common fluid reservoir. XL Tractor Hydraulic Fluid is manufactured with the highest quality base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant.

FEATURES & BENEFITS

- | | |
|--|---|
| 01 Meets the needs of modern tractors for a combination lubricant. | 02 Performs many functions such as lubrication of the transmission and final drive. |
| 03 Serving as hydraulic fluid for the operation of power steering units, brakes and implements. | 04 Eliminates "chatter" and excessive brake facing wear, assuring smooth operation of clutch packs and wet brakes. |
| 05 Protects metal surfaces against scuffing and wear. | 06 Compatible with equipment manufacturer's proprietary fluids and other fluids of this type. |

APPLICATIONS

XL Tractor Hydraulic Fluid is recommended for use as a multi-functional fluid in all type of farm equipment and tractors. Suitable for Use: • AGCO – improved power fluid 821XL, Power Fluid 821 • API GL-4 (not recommended for hypoid gear oil applications) • John Deere – J20C, Quatrol®, Hy-gard® • Ford New Holland – ESN-M2C134-D, FNHA-2-C-201 • Massey Ferguson – M1135, M1141, M1143, M1145 • HTF 272843, 257541, 246634 • White Farm Equipment – Q-1826 • Case Corporation – JIC-143, JIC-145, MS 1206, MS 1207, MS 1209, MS 1210 • Oliver – Type 55 • Caterpillar – TO-2 • Renk Doromat - 873, 874 A/B • Allison C-4 • Kubota UDT • Komatsu Dresser • Versatile Specification 23M or 24M • International Harvester B6 • Volvo – VME, WB 101 • Fiat-Hesson Multi-G • ZF TE-ML-03E • And many others... ® - Quatrol and Hy-gard are registered trademarks of John Deere and not a specification. XL Tractor Hydraulic Fluid may be used where Quatrol or Hy-gard is called for.

* ALWAYS CONSULT YOUR OWNER’S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

PRODUCT SPECIFICATIONS	RESULTS
Specific Gravity @ 60 °F	0.8690
Viscosity, Kinematic cSt at 40°C	55
Viscosity, Kinematic cSt at 100°C	9.4
Viscosity Index	152
Viscosity, Brookfield cP at -34.4°C	26,496
Flash Point, °F	450
Pour Point, °C (°F)	-39 (-38)
Color	1.5

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

CODES & AVAILABLE PRESENTATIONS

PG805-5GL

PureGuard XL Tractor Hydraulic Fluid

5 GAL

PERFORMANCE AT A GLANCE

VISCOSITY INDEX

152

FLASH POINT, °F

450

SPECIFIC GRAVITY @ 60 °F

0.8690

